





UT-6408CH

8口百兆非网管型以太网交换机 说明书

一、概述

UT-6408CH 8

二、面板描述



\$
%

mm

三、性能参数

3.1 标准

IEEE 802.3 10Base-T
IEEE 802.3u 100Base-TX

3.2 接口

RJ45 8 10/100Base-TX / MDI/MDI-X

LED PWR 1 8

3.3 电源需求

12/24/48VDC(10.8~52.8VDC)
100mA@24Vmax
1 3

3.4 交换性能

148810pps

MAC 1K

448Kb
1.6G

3.5 机械特性

IP40

W x H x D 100mm x 85mm x 40mm

3.6 工作环境

-40 75
-40 85
0 95% ()

3.7 行业标准

EMI FCC Part 15 Subpart B classA EN55022 class A

EMS

- IEC(EN)61000-4-2(ESD)
- IEC(EN)61000-4-3(RS)
- IEC(EN)61000-4-4(EFT)
- IEC(EN)61000-4-5(Surge)
- IEC(EN)61000-4-6(CS)
- IEC(EN)61000-4-8
- IEC 60068-2-27(Shock)
- IEC 60068-2-32(Freefall)
- IEC 60068-2-6(Vibration)

四、接口定义

4.1 10/100Base-TX

10/100Base-TX MDI/MDI-X

