





## 概述

UT-RT6212W-8T4GB-P110	4	M12	Bypass	4	M12	8	M12
		M12					
		EN50155				ESD	
	M12						

## 规格

SNMP v1/v2c/v3	RMON	-40	75
QoS LLDP DHCP Server	802.1Q Vlan	-40	85
		( 95% ( ) )	
IGMP-Snooping		180mm×170mm×60.2mm	
Single Couple			
NTP Client/Server			
100M( CAT5/CAT5e fl	100		
1000M( CAT6e/CAT7 fl	100	4kg	
		M4	
Link /ACT E1~E8 G1~G4( )		EMI FCC Part 15 Subpart B classA	EN55022 class A
RUN( )		EMS	
PWR( )		IEC(EN)61000-4-2(ESD)	
ALM( )		IEC(EN)61000-4-3(RS)	
	148810pps	IEC(EN)61000-4-4(EFT)	
	1488100pps	IEC(EN)61000-4-5(Surge)	
MAC	16K	IEC(EN)61000-4-6(CS)	
		IEC(EN)61000-4-8	
	56G	IEC 60068-2-27(Shock)	
12M		IEC 60068-2-32(Freefall)	
		IEC 60068-2-6(Vibration)	
	110VDC (66-160VDC)		
	15W		

