



三、主要特点

UT-6408M 8口百兆网管型以太网交换机 说明书

UT-6408M

4.1 协议标准

IEEE802.3 IEEE802.3u IEEE802.3x IEEE802.1Q
 IEEE802.1p IEEE802.1D IEEE802.1W IEEE802.1s
 IEEE802.1x IEEE802.3ad IEEE802.1ad
 ARP ICMP TCP HTTP HTTPS Telnet STP/RSTP/
 MSTP VLAN LLDP UT-Ring ACL IGMP-Snooping
 SNMPv1/v2c/v3 DHCP Server NTP Syslog Link Flap UDLD
 RMON LACP DHCP
 IEEE802.3x

4.2 接口

RJ45 8 10/100Base-T(X) /
 MDI/MDI-X
 LED PWR RUN ALM
 RJ45

4.3 传输距离

RJ45 100m

4.4 交换性能

148810pps

MAC 2K

1Mbit

2G

1632B

4.5 电源需求

12/24/48 VDC (10.8 to 52.8VDC)

150mA@24Vmax

4.6 机械特性

IP40

4.7 行业标准

EMI FCC Part 15 CISPR (EN55022) class A

EMS IEC(EN)61000-4-2(ESD)

IEC(EN)61000-4-3(RS)

IEC(EN)61000-4-4(EFT)

IEC(EN)61000-4-5(Surge)

IEC(EN)61000-4-6(CS)

IEC(EN)61000-4-8


IEC 60068-2-27(Shock)

IEC 60068-2-32(Freefall)

七、安装指导

7.1


7.2



7.3




7.4



八、管理系统登录

- 1 Console 115200 8-N-1
PIN3—TXD PIN4/5—GND PIN6-RXD
- 2 Web IP 192.168.1.254
admin
admin



九、包装清单

	1PCS
	1PCS
	6PCS
	2PCS
	1PCS
	1PCS
	1PCS