

全千兆网管型以太网交换机



UT-CN60-28GKWA系列

Web



全国统一服务热线：400 1144 149

8 7# 10
+86-755-81202008
+86-755-27886083
www.szutek.com





- SFP
- 100M 1000M
- IGMP Snooping
- IEEE 802.1Q VLAN
- QoS
- SNMP
- LLDP
- ACL
- STP/RSTP ERPS
- Z40~75



UT-CN60-28GKWA

24

console

Web

-40~75

EMC

协议标准

IEEE802.3 IEEE802.3u IEEE802.3x IEEE802.3z
 IEEE802.1Q IEEE802.1p IEEE 802.1D IEEE 802.1w
 ITU-T G.8032
 ARP ICMP TCP HTTP Telnet LLDP IGMP Snooping
 STP/RSTP ERPS SNMP
 IEEE802.3x

接口

100Base-FX/1000Base-X (SFP)
 RJ45 10/100/1000Base-T MDI/MDI-X
 LED RJ45

传输距离

100m

1310nm 20/40/60Km
 1550nm 80/100/120Km
 1310nm 2Km

交换性能

1488095pps

MAC

8K
 3Mb
 56G
 9600B

电源需求

110/220VAC(88~264VAC)/50-60Hz or 110/220VDC
 (88~264VDC)

功耗

15.5W
 30W

机械特性

IP40
 3.5kg

W×H×D : 440mm×44mm×295mm

工作环境

-40 ~75
 -40 ~85
 0~95%

行业标准

EMI: FCC Part 15 Subpart B classA EN55022 class A
 EMS:
 IEC(EN)61000-4-2(ESD)
 IEC(EN)61000-4-3(RS)
 IEC(EN)61000-4-4(EFT)
 IEC(EN)61000-4-5(Surge)
 IEC(EN)61000-4-6(CS)
 IEC(EN)61000-4-8
 IEC 60068-2-27(Shock)
 IEC 60068-2-32(Freefall)
 IEC 60068-2-6(Vibration)

