

百兆网络光纤收发器



UT-2602系列



全国统一服务热线: 400 1144 149

8 7# 10
+86-755-81202008
+86-755-27886083
www.szutek.com



-
-
- 10Mbps 100Mbps
-
-
- -40 85
- 12/24/48VDC(10.8-52.8VDC)
- SC ST FC SFP



UT-2602

10/100Base-TX

-40~85

EMC

标准

IEEE 802.3 IEEE 802.3u IEEE 802.3x

接口

	100Base-FX		SC	ST	FC	SFP	
RJ45	10/100Base-TX						MDI/
MDI-X							
LED	PWR	FDX		RJ			

交换性能

148810pps

MAC

1K
0.5Mb
1.2G

电源需求

12/24/48VDC(10.8-52.8VDC)
100mA@24Vmax

机械特性

IP40

机械尺寸

100mm x 80mm x 35mm

包装尺寸

180mm x 140mm x 45mm

工作环境

-40 85
-40 85
95%

行业标准

EMI FCC Part 15 Subpart B classA EN55022 class A
EMS
IEC(EN)61000-4-2(ESD)

IEC(EN)61000-4-3(RS)

尺寸



	10/100Base-TX	100Base-FX	
UT-2602SM-SC	2	1	SC
UT-2602SM-ST	2	1	ST
UT-2602SM-FC	2	1	FC
UT-2602MM-SC	2	1	SC
UT-2602MM-ST	2	1	ST
UT-2602MM-FC	2	1	FC
UT-2602P	2	1	SFP

备注:

SC 20KM " SM" " MM" " R" (" T" (UT-2602RSM-SC