

百兆网络光纤收发器



UT-2574系列

&



全国统一服务热线：400 1144 149

8 7# 10
+86-755-81202008
+86-755-27886083
www.szutek.com



-
-
- 10Mbps 100Mbps
-
-
- 12/24/48VDC(10.8~52.8VDC)
- SC ST FC SFP



UT-2574 列兆光发器供 10/100Base-TX以 口和1 100Base-FX光口 于以 口光
 合化区光到 器列产品 -20~75 作和 EMC 兼 保
 劣之互作列传 可以便 务器器器
 供全可决

标准:
 IEEE 802.3 10Base-T
 IEEE 802.3u 100Base-TX和100Base-FX
接口:
 光 1 100Base-FX 可 SC ST FC SFP
 RJ45 10/100Base-TX 动侦 全/半双 MDI/MDI-X
 LED 1 PWR RJ-45 FDX光

传输距离
 五双 100m
 光
 单 1310nm 20/40/60Km
 1550nm 80/100/120Km
 1310nm 2Km

交换性能
 发 148810pps
 传 储发
 MAC 1K
 448Kb
 1G

电源需求
 入压 12/24/48VDC(10.8~52.8VDC)
 功 200mA@24Vmax
 1 可 3
 保 供
 反 保 供

机械特性:
 IP40

机械尺寸:
 150mm x 100mm x 37mm

包装尺寸:
 250mm x 205mm x 55mm

工作环境:
 作 -20 75
 储 -40 85
 0 95%

行业标准:
 EMI FCC Part 15 Subpart B class A EN55022 class A
 EMS
 IEC(EN)61000-4-2(ESD)



