

:

Model:UT-CN8302

USB RS-485/422

1.

- UTEK
-
- Logo 

2.

- UT-CN8302
- VER: 01

3.

UT-CN8302	USB	RS-485/422			
USB RS-422 RS-485		USB		RS-422	RS-485
600w					

RS-422/RS-485

UT-CN8302					
128 RS-422 RS-485				300-921.6Kbps	
			USB	RS-422	USB
				RS-485	

4.

- 1 USBV1.1 1.0 2.0 EIA RS-485 RS-422
- 2 USB VCC DATA+ DATA- GND FG
- 3 RS-485 T/R+ T/R- GND
- 4 RS-422 T/R+ T/R- RXD+ RXD- GND
- 5 2 4
- 6 ,
- 7 300-921.6Kbps,
- 8 128 RS-422 RS-485
- 9 RS-485/422 1200 (9600bps),USB 5
- 10 600w ±15KV 8KV
- 11 USB A ,DB9

12	3	PWR	TXD	RXD
13				
14	921600bps	100m		
	38400bps	600m		
	9600bps	1.2Km		
15	1555mm×36mm×16mm	×	×	
16	-45	85	5%	95%
17	0-1200			
18	Win/11,10,8,7,VISTA,XP/SERVER 2022,2019,2016,2012,2008,2003/Linux			

5.

1、DB9针型：RS-485/RS-422输出信号及接线端子引脚分配

DB9 针型 输出信号	输出信号	RS-422 半双工接线	RS-485 半双工接线	RS-485 全双工接线	（GND）
[Redacted content]					

6.



7. ()

8.

9.

10.

S	
	1PCS
	1PCS
	1PCS
	1PCS

11.

177*108*28mm± 1mm

:

12.

-40 +85 , 5% 95%

13. / /

14.

15.